

19

which controls the memory **1410**, an interface **1430** for connection with an external device, and so on. The memory system **1400** may be a card type such as a solid state disk (SSD), a USB memory (universal serial bus memory), a secure digital (SD) card, a mini secure digital (mSD) card, a micro secure digital (micro SD) card, a secure digital high capacity (SDHC) card, a memory stick card, a smart media (SM) card, a multimedia card (MMC), an embedded MMC (eMMC), a compact flash (CF) card, and so on.

The memory **1410** for storing data may include one or more of the above-described semiconductor devices in accordance with the implementations.

Also, the memory **1410** according to the present implementation may further include a ROM (read only memory), a NOR flash memory, a NAND flash memory, a phase change random access memory (PRAM), a resistive random access memory (RRAM), a magnetic random access memory (MRAM), and so on, which have a nonvolatile characteristic.

The memory controller **1420** may control exchange of data between the memory **1410** and the interface **1430**. To this end, the memory controller **1420** may include a processor **1421** for performing an operation for and processing commands inputted through the interface **1430** from an outside of the memory system **1400**.

The interface **1430** is to perform exchange of commands and data between the memory system **1400** and the external device. The interface **1430** may be compatible with interfaces which are used in devices, such as a USB memory (universal serial bus memory), a secure digital (SD) card, a mini secure digital (mSD) card, a micro secure digital (micro SD) card, a secure digital high capacity (SDHC) card, a memory stick card, a smart media (SM) card, a multimedia card (MMC), an embedded MMC (eMMC), a compact flash (CF) card, and so on, or be compatible with interfaces which are used in devices similar to the above mentioned devices. The interface **1430** may be compatible with one or more interfaces having a different type from each other.

The memory system **1400** according to the present implementation may further include a buffer memory **1440** for efficiently transferring data between the interface **1430** and the memory **1410** according to diversification and high performance of an interface with an external device, a memory controller and a memory system. For example, the buffer memory **1440** for temporarily storing data may include one or more of the above-described semiconductor devices in accordance with the implementations.

Moreover, the buffer memory **1440** according to the present implementation may further include an SRAM (static random access memory), a DRAM (dynamic random access memory), and so on, which have a volatile characteristic, and a phase change random access memory (PRAM), a resistive random access memory (RRAM), a spin transfer torque random access memory (STTRAM), a magnetic random access memory (MRAM), and so on, which have a nonvolatile characteristic. Unlike this, the buffer memory **1440** may not include the semiconductor devices according to the implementations, but may include an SRAM (static random access memory), a DRAM (dynamic random access memory), and so on, which have a volatile characteristic, and a phase change random access memory (PRAM), a resistive random access memory (RRAM), a spin transfer torque random access memory (STTRAM), a magnetic random access memory (MRAM), and so on, which have a nonvolatile characteristic.

At least one of the memory **1410**, the memory controller **1420**, the interface **1430** and the buffer memory **1440** may

20

include one or more of the above-described semiconductor devices in accordance with the implementations. For example, at least one of the memory **1410**, the memory controller **1420**, the interface **1430** and the buffer memory **1440** may include a transistor comprising a gate where at least a portion of the gate is filled in a semiconductor substrate including an active region defined by an isolation layer; a junction which is disposed over the active region at both side of the gate and includes a metal-containing layer and a first semiconductor layer doped with an impurity and interposed between the active region and the metal-containing layer; and a material layer which is interposed between the junction and the active region to prevent diffusion of the impurity from the first semiconductor layer and defines an opening for coupling the junction to the active region. Through this, operating characteristics of at least one of the memory **1410**, the memory controller **1420**, the interface **1430** and the buffer memory **1440** may be improved. As a consequence, operating characteristics of the memory system **1400** may be improved.

Features in the above examples of electronic devices or systems in FIGS. 9-13 based on the memory devices disclosed in this document may be implemented in various devices, systems or applications. Some examples include mobile phones or other portable communication devices, tablet computers, notebook or laptop computers, game machines, smart TV sets, TV set top boxes, multimedia servers, digital cameras with or without wireless communication functions, wrist watches or other wearable devices with wireless communication capabilities.

While this patent document contains many specifics, these should not be construed as limitations on the scope of any invention or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular inventions. Certain features that are described in this patent document in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Moreover, the separation of various system components in the embodiments described in this patent document should not be understood as requiring such separation in all embodiments.

Only a few implementations and examples are described. Other implementations, enhancements and variations can be made based on what is described and illustrated in this patent document.

What is claimed is:

1. An electronic device comprising a transistor, wherein the transistor comprises:

- a substrate including an active region and an isolation layer which defines the active region;
- a gate formed on the substrate to include at least a portion of the gate which is filled in the substrate;
- a junction which is disposed over the active region at both sides of the gate and includes a metal-containing layer